

12 ch ECG



Interpretive 12 Channel Resting  
ECG with Color LCD Touch Screen

# CardioTouch 3000

- \* Convenient A4 size print-outs allow for easy chart filing
- \* Grid function allows you to use low cost plain fax paper
- \* One-touch operation (monitoring, recording mode)
- \* 12Ch simultaneous display
- \* Wide and Clear Color TFT LCD
- \* Touch screen for easy operation
- \* Rotary Key Access to All Menus

- 12channel interpretive ECG
- Over 130 kinds of interpretation results based on advanced Minnesota code
- Memory for up to 120 patients
- Real-time preview monitor
- PC compatible through LAN
- Multi-language(English,Russian,French, German,Italian,Chinese,Spanish,Turkish)available
- Lead fault message
- Pace maker detection



# SPECIFICATIONS

## ECG >>>

<b>ECG leads</b>	10 lead, 12 channel simultaneous ECG and acquisition
<b>Dimension</b>	296(W) × 305.5(H) × 92.5(D)mm, approx.3.5kg
<b>Recording channel</b>	3 channels, 6 channels, 12 channels, 60 second 1 channel and beat report
<b>Sensitivity</b>	2.5, 5, 10, 20, auto(I~aVF: 10, V1~V6: 5) mm/mV
<b>Printing speed</b>	12.5, 25, 50 mm/s
<b>Sampling rate</b>	500 samples/sec
<b>Filters</b>	AC(50/60 Hz, -20 dB or better) Muscle(25~35 Hz, -3 dB or better) Base line drift(0.1 Hz, -3 dB or better) Low pass filter : off, 40 Hz, 100 Hz, 150 Hz
<b>Display</b>	480 X 272 Color TFT LCD Display, 3 and 12 channels preview ECG wave
<b>Monitor display</b>	ID, date, sensitivity, speed, filter, form, rhythm lead
<b>User interface</b>	Touch screen(Alphanumeric and symbol available), Keyboard, rotary push-knob(pop-up menu)
<b>Patient data</b>	ID, name, age, sex, height, weight, smoke, race
<b>Basic measurement</b>	Heart rate, PR int, QRS dur, QT/QTc, P-R-T axis
<b>Recorder</b>	Thermal print head, roll paper Report papers : width : A4 : 210mm or 8.5" / length : A4 : 300mm or 11" Resolution : vertical : 8dot/mm / horizontal : 16dot/mm
<b>Electrical</b>	Internal noise: 20 $\mu$ V (p-p)max / Input circuit : floating input Input impedance : $\geq 10M \Omega$ / Input voltage range : $\geq \pm 5mV$ Common mode rejection : $> 100 dB$ / DC offset voltage : $\geq \pm 300mV$ Time constant : 3.2sec / Patient leakage current : $< 10\mu A$ Frequency response : 0.05 ~ 150 Hz / Isolated and defibrillation protected
<b>Signal quality control</b>	Disconnected lead detection, Pacemaker pulse detection
<b>ECG data storage</b>	storage for 120 ECGs (Internal on flash memory)
<b>Power</b>	Power supply : AC or built-in battery(option) 95 ~ 240 VAC, 50/60 Hz, 1.0 ~ 0.5A, 60W max
<b>Battery(Ni-MH)</b>	1 hour of normal use (approx. 100 ECG printouts)
<b>Communication</b>	PC connection with RS232 interface and LAN
<b>Safety conformity</b>	Class I, Type BF, CE, CSA, FDA, KFDA, SFDA, CCC
<b>Environment</b>	Operating humidity : 30~85% / Operating temperature : 10 ~ 40 $^{\circ}C$ Atmospheric pressure : 70 ~ 106KPa
<b>Standard accessory</b>	Power cord 1 EA, Patient cable 1 EA, Limb 1 set(4 EA), Chest ball 1 set(6 EA), Chart paper 1 EA, Operation manual 1 EA
<b>Options</b>	Rechargeable battery, Cart, Hanger, Bag, PC S/W

\* Specifications can be changed without prior notification.



**Main office : Bionet Co.,Ltd.**  
Tel : +82-2-6300-6418(Int'l)  
e-mail : sales@ebionet.com(Int'l)

**North America : Bionet America, Inc.**  
Tel : +1-714-734-1760

**Europe : MGB Endoskopische Ger-te GmbH Berlin**  
Tel : +49-30-6392-7010

**China : Bionet China**  
Tel : +86-10-58220564

**www.ebionet.com**  
+82-2-6300-6477(Domestic)  
yunms@ebionet.com(Domestic)

**www.bionetus.com**  
e-mail : sales@bionetus.com

**www.mgb-berlin.de**  
e-mail : info@mgb-berlin.de

e-mail : sales-china@ebionet.com